According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:
1.3	07.03.2022	400001021215

Enriching lives through innovation

Date of last issue: 26.10.2020 Date of first issue: 06.12.2017

Print Date 17.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: ARALDITE® RAPID RESIN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	: Epoxy constituents
Substance/Mixture	

1.3 Details of the supplier of the safety data sheet

Company Address	 Huntsman Advanced Materials (Europe)BVBA Everslaan 45 3078 Everberg Belgium
Telephone Telefax	: +41 61 299 20 41 : +41 61 299 20 40
E-mail address of person responsible for the SDS	: Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number	:	EUROPE: +32 35 75 1234
		France ORFILA: +33(0)145425959
		ASIA: +65 6336-6011
		China: +86 20 39377888
		+86 532 83889090
		India: + 91 22 42 87 5333
		Australia: 1800 786 152
		New Zealand: 0800 767 437
		USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)				
Skin irritation, Category 2	H315: Causes skin irritation.			
Eye irritation, Category 2	H319: Causes serious eye irritation.			
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.			
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.			

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN



Enriching lives through innovation

Version 1.3	Revision Date: 07.03.2022	-	DS Number: 00001021215	Date of last issue: 26.10.2020 Date of first issue: 06.12.2017
				Print Date 17.06.2022
Hazar	d pictograms	:		
Signal	word	:	Warning	
Hazar	d statements	:	H315 H317 H319 H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
Preca	utionary statements	:	Prevention: P261 P264 P273 P280	Avoid breathing mist or vapours. Wash skin thoroughly after handling. Avoid release to the environment. Wear protective gloves/ eye protection/ face protection.
			Response: P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
			P391	Collect spillage.

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane

1,4-bis(2,3 epoxypropoxy)butane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concent ration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 603-073-00-2	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2;	>= 70 - < 90

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SDS Number:

400001021215

ARALDITE® RAPID RESIN

Version	Revision Date:
1.3	07.03.2022

Date of last issue: 26.10.2020 Date of first issue: 06.12.2017

Print Date 17.06.2022

HUNTSMAN

Enriching lives through innovation

		H411 specific concentration limit Skin Irrit. 2; H315 >= 5 % Eye Irrit. 2; H319 >= 5 %	
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Eye Dam. 1; H318 Acute toxicity estimate	>= 3 - < 10
		Acute dermal toxicity: 1,100 mg/kg	

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Treat symptomatically. Get medical attention if symptoms occur.
Protection of first-aiders	:	First Aid responders should pay attention to self-protection and use the recommended protective clothing If potential for exposure exists refer to Section 8 for specific personal protective equipment. Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
If inhaled	:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	:	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Immediately flush eye(s) with plenty of water.

SDS_GB-AM - 6N - 400001021215

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version 1.3	Revision Date: 07.03.2022	SDS Number: 400001021215	Date of last issue: 26.10.2020 Date of first issue: 06.12.2017
			Print Date 17.06.2022
			ct lenses. open while rinsing. persists, consult a specialist.
lf swa	allowed	• •	ry tract clear. thing by mouth to an unconscious person. ersist, call a physician.
	mportant symptoms known.	s and effects, both ac	ute and delayed
4.3 Indica Treat	•	te medical attention a : Treat symptom	atically.

SECTION 5: Firefighting measures

5.1	Extinguishing media		
	Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
	Unsuitable extinguishing media	:	Exercise caution when using a high volume water jet as it may scatter and spread fire
5.2	Special hazards arising from	the	substance or mixture
	Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
	Hazardous combustion products	:	Carbon oxides Halogenated compounds
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
	Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
	Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:
1.3	07.03.2022	400001021215

Date of last issue: 26.10.2020 Date of first issue: 06.12.2017

Print Date 17.06.2022

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Refer to protective measures listed in sections 7 and 8.
6.2 Environmental precautions		

Environmental precaution	ns :	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Advice on protection against Normal measures for preventive fire protection. ÷. fire and explosion Hygiene measures When using do not eat or drink. When using do not smoke. 2 Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated
place. Containers which are opened must be carefully
resealed and kept upright to prevent leakage. Keep in properly labelled containers.



DS Number: Date

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Enriching lives through innovation

ARALDITE® RAPID RESIN

Version 1.3	Revision Date: 07.03.2022		DS Number: 00001021215	Date of last issue: 26.10.2020 Date of first issue: 06.12.2017
				Print Date 17.06.2022
Adv	vice on common storage	:	For incompatible SDS.	materials please refer to Section 10 of this
	commended storage	:	2 - 40 °C	
Further information on storage stability		:	Stable under norr	nal conditions.
•	cific end use(s) ecific use(s)	:	No data available	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Out at an a start a			Detential health	Malua
Substance name	End Use	Exposure routes	Potential health effects	Value
bis-[4-(2,3- epoxipropoxi)phenyl]p ropane	Workers	Inhalation	Long-term systemic effects	4.93 mg/m3
	Workers	Dermal	Long-term systemic effects	0.75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.87 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.5 mg/kg bw/day
1,4-bis(2,3 epoxypropoxy)butane	Workers	Inhalation	Long-term systemic effects	4.7 mg/m3
	Workers	Dermal	Long-term systemic effects	6.66 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.16 mg/m3
	Consumers	Dermal	Long-term systemic effects	3.33 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.33 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
bis-[4-(2,3-	Fresh water	0.006 mg/l
epoxipropoxi)phenyl]propane		_
	Marine water	0.001 mg/l
	Fresh water sediment	0.341 mg/kg dry weight (d.w.)
	Marine sediment	0.034 mg/kg dry
		weight (d.w.)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version	Revisi
1.3	07.03.2

ion Date: SDS Number: 2022 400001021215

Date of last issue: 26.10.2020 Date of first issue: 06.12.2017

Print Date 17.06.2022

	Soil	0.065 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Secondary Poisoning	11 mg/kg
1,4-bis(2,3 epoxypropoxy)butane	Fresh water	0.024 mg/l
	Remarks:Assessment Factors	
	Marine water	0.002 mg/l
	Remarks:Assessment Factors	
	Sewage treatment plant	100 mg/l
	Remarks:Assessment Factors	
	Fresh water sediment	0.084 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Marine sediment	0.008 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Soil	0.003 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Oral	0.028 mg/kg

8.2 Exposure controls

Personal protective equipment

Fersonal protective equipme		
Eye protection	ve wash bottle with pure water ghtly fitting safety goggles 'ear face-shield and protective suit for abn oblems.	ormal processing
Hand protection Material Break through time	ityl-rubber 8 h	
Material Break through time	trile rubber) - 480 min	
Material Break through time	hyl Vinyl Alcohol Laminate (EVAL) 8 h	
Remarks	hemical-resistant, impervious gloves comported standard should be worn at all time memical products if a risk assessment indice ecessary. The suitability for a specific worl scussed with the producers of the protection be selected protective gloves have to satis becifications of Regulation (EU) 2016/425 N 374 derived from it. Gloves should be dis placed if there is any indication of degrads eakthrough. Take note of the information oducer concerning permeability and breat and of special workplace conditions (mecha- uration of contact).	tes when handling cates this is cplace should be ve gloves. Sfy the and the standard scarded and ation or chemical given by the c through times,
Skin and body protection	npervious clothing	



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Enriching lives through innovation

ARALDITE® RAPID RESIN

Version 1.3	Revision Date: 07.03.2022	SDS Number: 400001021215	Date of last issue: 26.10.2020 Date of first issue: 06.12.2017
			Print Date 17.06.2022
			y protection according to the amount and no f the dangerous substance at the work place.
Resp	iratory protection	ventilation is that exposur	ory protection unless adequate local exhaust provided or exposure assessment demonstrates es are within recommended exposure guidelines. hould conform to EN 14387
Fi	lter type	: Combined p	articulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	light yellow
Odour	:	No data is available on the product itself.
Odour Threshold	:	No data is available on the product itself.
рН	:	No data is available on the product itself.
Melting point/freezing point	:	No data is available on the product itself.
Boiling point	:	No data is available on the product itself.
Flash point	:	> 200 °C Method: Pensky-Martens closed cup
Flammability (solid, gas)	:	No data is available on the product itself.
Upper explosion limit / Upper flammability limit	:	No data is available on the product itself.
Lower explosion limit / Lower flammability limit	:	No data is available on the product itself.
Vapour pressure	:	No data is available on the product itself.
Relative vapour density	:	No data is available on the product itself.
Relative density	:	No data is available on the product itself.
Density	:	No data is available on the product itself.
Solubility(ies) Water solubility	:	No data is available on the product itself.
Solubility in other solvents	:	No data is available on the product itself.
Partition coefficient: n- octanol/water	:	No data is available on the product itself.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Enriching lives through innovation

ARALDITE® RAPID RESIN

Version 1.3	Revision Date: 07.03.2022	SDS Number: 400001021215	Date of last issue: 26.10.2020 Date of first issue: 06.12.2017
			Print Date 17.06.2
Auto-	ignition temperature	: No data is ava	ailable on the product itself.
Deco	mposition temperature	: No data is ava	ailable on the product itself.
Visco	sity	: No data is ava	ailable on the product itself.
9.2 Other	information		
No da	ata available		
SECTION	N 10: Stability and re	eactivity	
10.1 Read	tivity		
No da	angerous reaction know	n under conditions o	f normal use.
10.2 Cher	nical stability		
Stabl	e under normal conditio	ons.	
10.3 Poss	bility of hazardous re	eactions	
Haza	rdous reactions	: No hazards to	be specially mentioned.
10.4 Cond	litions to avoid		
Cond	itions to avoid	: None known.	
10.5 Incoi	mpatible materials		
Mate	rials to avoid	: None known.	
10.6 Haza	rdous decomposition	products	
Haza produ	rdous decomposition Icts	: carbon dioxid carbon mono: Halogenated	kide

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity		
Product:		
Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:
1.3	07.03.2022	400001021215

Print Date 17.06.2022

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane: Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

		Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	:	LD50 (Rat, male and female): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

1,4-bis(2,3 epoxypropoxy)butane:

1,4-bis(2,3 epoxypropoxy)butane:			
Acute oral toxicity :	LD50 (Rat, male and female): 1,163 mg/kg Method: OECD Test Guideline 401 GLP: yes Assessment: The component/mixture is moderately toxic after single ingestion.		
Acute inhalation toxicity :	LC50 (Rat): > 2.068 mg/l Exposure time: 4 h Test atmosphere: dust/mist		
	Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is moderately toxic after short term inhalation.		
Acute dermal toxicity :	Acute toxicity estimate: 1,100 mg/kg Method: Converted acute toxicity point estimate		
	Assessment: The component/mixture is moderately toxic after single contact with skin.		

Skin corrosion/irritation

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Species :	Rabbit
Exposure time :	4 h
Assessment :	Irritating to skin.
Method :	OECD Test Guideline 404
Result :	Irritating to skin.

1,4-bis(2,3 epoxypropoxy)butane:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Skin irritation
GLP	:	yes



Enriching lives through innovation

Date of last issue: 26.10.2020 Date of first issue: 06.12.2017

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:
1.3	07.03.2022	400001021215

HUNTSMAN Enriching lives through innovation

Date of last issue: 26.10.2020 Date of first issue: 06.12.2017

Print Date 17.06.2022

Serious eye damage/eye irritation

Product:

Species:Not AssignedMethod:OECD Test Guideline 437Result:Eye irritation

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Species	:	Rabbit
Assessment	:	Irritating to eyes.
Method	:	OECD Test Guideline 405
Result	:	Irritating to eyes.

1,4-bis(2,3 epoxypropoxy)butane:

Species	:	Rabbit
Assessment	:	Risk of serious damage to eyes.
Method	:	OECD Test Guideline 405
GLP	:	yes

Respiratory or skin sensitisation

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Test Type	:	Local lymph node assay (LLNA)
Exposure routes	:	Skin
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	The product is a skin sensitiser, sub-category 1B.

1,4-bis(2,3 epoxypropoxy)butane:

Exposure routes	:	Skin
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	May cause sensitisation by skin contact.
GLP	:	yes

Assessment

: Harmful if inhaled.

Germ cell mutagenicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Test system: mouse lymphoma cells Metabolic activation: without metabolic activation Result: positive
	Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Regulation	s SI 2019/758	-,	Enriching lives through innov
ARALI	DITE® RAPID	RESIN	
Version 1.3	Revision Date: 07.03.2022	SDS Number: 400001021215	Date of last issue: 26.10.2020 Date of first issue: 06.12.2017
			Print Date 17.06
			/
Geno	otoxicity in vivo	: Test Type: in v Species: Mous Cell type: Gern Application Ro Dose: 3333, 10 Result: negativ	e (male) n ute: Oral 000 mg/kg
		Species: Rat (r Cell type: Som Application Ro Dose: 50,250,5	atic ute: Oral 600,1000 mg/kg bw/day 9 Test Guideline 488
1,4-b	is(2,3 epoxypropoxy	/)butane:	
Geno	toxicity in vitro	Concentration: Metabolic activ Method: OECE Result: positive GLP: yes	erse mutation assay 10 - 5000 ug/plate ation: with and without metabolic activation Test Guideline 471 classified due to data which are conclusive

data which are conclusive although insufficient for classification. Test Type: Chromosome aberration test in vitro Test system: Chinese hamster lung cells Concentration: 1 - 100 µg/L Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 473 Result: positive GLP: yes Remarks: Not classified due to data which are conclusive although insufficient for classification. Test Type: In vitro mammalian cell gene mutation test Test system: Chinese hamster lung cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 **Result:** positive GLP: no Remarks: Not classified due to data which are conclusive although insufficient for classification. Test Type: In vivo micronucleus test Genotoxicity in vivo Species: Mouse (male) Cell type: Somatic Application Route: Oral

Exposure time: 4 d

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH

ŀ



Enriching lives through innovation

Print Date 17.06.2022

SAFETY DA	TA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version 1.3	Revision Date: 07.03.2022	SDS Number: 400001021215	Date of last issue: 26.10.2020 Date of first issue: 06.12.2017
			Print Date 17.06.2022
		Dose: 187.5 - 75 Method: OECD Result: negative GLP: yes	Test Guideline 474
		Species: Rat Cell type: Liver of Application Rout	te: Oral Test Guideline 486
	m cell mutagenicity- essment		nce does not support classification as a germ nimal testing did not show any mutagenic
Car	cinogenicity		
<u>Con</u>	nponents:		
	[4-(2,3-epoxipropoxi)ph	enyl]propane:	
Spe App Exp Dos Frec NO/ Met Res Tar Spe App Exp Dos Frec NOE Met Res	cies lication Route osure time e quency of Treatment AEL hod ult get Organs cies lication Route osure time e quency of Treatment EL hod	 Rat, male Oral 24 month(s) 0, 2, 15, or 100 m 7 days/week 15 mg/kg bw/day OECD Test Guid negative Digestive organs Mouse, male Dermal 24 month(s) 0, 0.1, 10, 100 m 3 days/week 0.1 mg/kg body OECD Test Guid negative Digestive organs 	y deline 453 s ng/kg bw/day weight deline 453
Exp Dos Frec NOE Meti Res Spe App	lication Route osure time e quency of Treatment EL hod ult	 Rat, female Dermal 24 month(s) 0.1, 100, 1000 m 5 days/week 100 mg/kg body OECD Test Guid negative Rat, female Oral 24 month(s) 	weight
Dos		: 24 month(s) : 0, 2, 15, or 100 r : 7 days/week	mg/kg bw/day



Version

1.3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SDS Number:

400001021215

ARALDITE® RAPID RESIN Revision Date:

07.03.2022

	Print Date 17.06.2022
NOAEL Method Result Target Organs	 100 mg/kg bw/day OECD Test Guideline 453 negative Digestive organs
Species Application Route Exposure time Dose Frequency of Treatment NOEL Method Result Target Organs	 Rat, females Oral 24 month(s) 0, 2, 15, or 100 mg/kg bw/day 7 days/week 2 mg/kg bw/day OECD Test Guideline 453 negative Digestive organs
Reproductive toxicity	
Components:	
bis-[4-(2,3-epoxipropoxi)phe	enyl]propane:
Effects on fertility	 Test Type: Two-generation study Species: Rat, male and female Application Route: Oral Dose: 0, 50, 180, 540 or 750 milligram per kilogram Duration of Single Treatment: 238 d Frequency of Treatment: 1 daily General Toxicity - Parent: NOEL: 540 mg/kg body weight General Toxicity F1: NOEL: 750 mg/kg body weight Symptoms: No adverse effects Method: OECD Test Guideline 416 Result: No effects on fertility and early embryonic development were detected.
Effects on foetal development	 Species: Rabbit, female Application Route: Dermal Dose: 0, 30, 100 or 300 milligram per kilogram Duration of Single Treatment: 28 d Frequency of Treatment: 1 daily General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight Method: Other guidelines Result: No teratogenic effects Test Type: Pre-natal Species: Rabbit, female Application Route: Oral Dose: 0, 20, 60 or 180 milligram per kilogram Duration of Single Treatment: 13 d

Frequency of Treatment: 1 daily General Toxicity Maternal: NOAEL: 60 mg/kg body weight Developmental Toxicity: NOAEL: 180 mg/kg body weight Method: OECD Test Guideline 414 Result: No teratogenic effects

Test Type: Pre-natal



Enriching lives through innovation

Date of last issue: 26.10.2020

Date of first issue: 06.12.2017

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version	Revision Date:
1.3	07.03.2022

Date of last issue: 26.10.2020 Date of first issue: 06.12.2017

Print Date 17.06.2022

Species: Rat, female Application Route: Oral Dose: 0, 60, 180 and 540 milligram per kilogram Duration of Single Treatment: 10 d Frequency of Treatment: 1 daily General Toxicity Maternal: NOAEL: 180 mg/kg body weight Developmental Toxicity: NOAEL: > 540 mg/kg body weight Method: OECD Test Guideline 414 Result: No teratogenic effects

1,4-bis(2,3 epoxypropoxy)butane:

Effects on foetal development	 Test Type: Pre-natal Species: Rat, female Application Route: Oral Dose: 0/30/100/300 mg/kg bw/day Duration of Single Treatment: 17 d General Toxicity Maternal: NOAEL: 300 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight Method: OECD Test Guideline 414 GLP: yes Remarks: Information given is based on data obtained from
	Remarks: Information given is based on data obtained from similar substances.

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Species NOAEL Application Route Exposure time Number of exposures Dose Method	:	Rat, male and female 50 mg/kg oral (gavage) 14 Weeks 7 d 0, 50, 250, 1000 mg/kg/day OECD Test Guideline 408
Species NOAEL Application Route Exposure time Number of exposures Dose Method	:	Rat, male and female >= 10 mg/kg Skin contact 13 Weeks 5 d 0, 10, 100, 1000 mg/kg/day OECD Test Guideline 411
Species NOAEL Application Route Exposure time Number of exposures		Mouse, male 100 mg/kg Skin contact 13 Weeks 3 d



SDS Number: 400001021215 According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN



Enriching lives through innovation

Version 1.3	Revision Date: 07.03.2022	SDS Number: 400001021215		Date of last issue: 26.1 Date of first issue: 06.1	0.2020
					Print Date 17.06.2022
Dose Method		:	0, 1, 10, 100 mg/k OECD Test Guide		
1,4-bis	(2,3 epoxypropoxy)bı	utan	e:		
Exposu	tion Route re time r of exposures		Rat, male and fem 200 mg/kg Oral 28 d daily 25, 100, 200, 400 Subacute toxicity		

Species	: Rat, male and female
NOAEL	: 263 mg/kg
Application Route	: Oral
Exposure time	: 90 h
Number of exposures	: daily
Dose	: 0,30,100,300 mg/kg bw/day
Method	: OECD Test Guideline 408
GLP	: yes
Remarks	: Information given is based on data obtained from similar substances.

Aspiration toxicity

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:
1.3	07.03.2022	400001021215

Date of last issue: 26.10.2020 Date of first issue: 06.12.2017

Print Date 17.06.2022

SECTION 12: Ecological information

12.1 Toxicity

Components:						
bis-[4-(2,3-epoxipropoxi)phen	yl]propane:					
Toxicity to fish :	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203					
Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia magna (Water flea)): 1.8 mg/l Exposure time: 48 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 202					
Toxicity to algae/aquatic : plants	EC50 : 11 mg/l Exposure time: 72 h Test Type: static test Test substance: Fresh water Method: EPA-660/3-75-009					
	NOEC : 4.2 mg/l Exposure time: 72 h Test Type: static test Test substance: Fresh water Method: EPA-660/3-75-009					
Toxicity to microorganisms	IC50 (activated sludge): > 100 mg/l Exposure time: 3 h Test Type: static test Test substance: Fresh water					
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEC: 0.3 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Test substance: Fresh water Method: OECD Test Guideline 211					
Ecotoxicology Assessment						
Chronic aquatic toxicity :	Toxic to aquatic life with long lasting effects.					
1,4-bis(2,3 epoxypropoxy)butane:						
Toxicity to fish	LC50 (Brachydanio rerio (zebrafish)): 24 mg/l End point: mortality Exposure time: 96 h Test Type: static test Analytical monitoring: no Test substance: Fresh water Method: OECD Test Guideline 203					

GLP: no



e: SDS Number:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SDS Number:

400001021215

ARALDITE® RAPID RESIN Revision Date:

07.03.2022

Version

1.3

Toxicity to daphnia and other aquatic invertebrates	 EC50 (Daphnia magna (Water flea)): 75 mg/l End point: Immobilization Exposure time: 24 h Test Type: static test Analytical monitoring: no Test substance: Fresh water Method: OECD Test Guideline 202 GLP: no
Toxicity to algae/aquatic plants	 EL50 (Pseudokirchneriella subcapitata (green algae)): > 160 mg/l Exposure time: 72 h Test Type: static test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 201 GLP: yes
	NOELR (Pseudokirchneriella subcapitata (green algae)): 40 mg/l Exposure time: 72 h Test Type: static test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 201 GLP: yes
Toxicity to microorganisms	 IC50 (activated sludge): > 100 mg/l Exposure time: 3 h Test Type: static test Analytical monitoring: no Test substance: Fresh water Method: OECD Test Guideline 209 GLP: no
12.2 Persistence and degradabilit	y
Components:	
bis-[4-(2,3-epoxipropoxi)pher	
Biodegradability	 Test Type: aerobic Inoculum: activated sludge, non-adapted Concentration: 20 mg/l Result: Not readily biodegradable. Biodegradation: 5 % Exposure time: 28 d Method: OECD Test Guideline 301F
Stability in water	 Degradation half life (DT50): 4.83 d (25 °C) pH: 4 Method: OECD Test Guideline 111 Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)



Enriching lives through innovation

Print Date 17.06.2022

Date of last issue: 26.10.2020

Date of first issue: 06.12.2017

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version	Revision Date:
1.3	07.03.2022

Date of last issue: 26.10.2020 Date of first issue: 06.12.2017

Print Date 17.06.2022

pH: 9 Method: OECD Test Guideline 111 Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C) pH: 7 Method: OECD Test Guideline 111 Remarks: Fresh water

1,4-bis(2,3 epoxypropoxy)butane:

Biodegradability	:	Test Type: aerobic Inoculum: activated sludge Concentration: 20 mg/l Result: Not readily biodegradable. Biodegradation: 43 % Exposure time: 28 d Method: OECD Test Guideline 301F GLP: yes
		Test Type: aerobic

I lost Type: aerobic Inoculum: Sewage (STP effluent) Concentration: 20 mg/l Result: Not readily biodegradable. Biodegradation: 38 % Related to: Dissolved organic carbon (DOC) Exposure time: 28 d Method: OECD Test Guideline 301E GLP: no

12.3 Bioaccumulative potential

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Bioaccumulation	:	Bioconcentration factor (BCF): 31 Remarks: Does not bioaccumulate.
Partition coefficient: n- octanol/water	:	log Pow: 3.242 (25 °C) pH: 7.1 Method: OECD Test Guideline 117

1,4-bis(2,3 epoxypropoxy)butane:

Partition coefficient: n-	:	log Pow: -0.269 (25 °C)
octanol/water		pH: 6.7
		Method: OECD Test Guideline 117
		GLP: yes

12.4 Mobility in soil

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane: Distribution among : Koc: 445 environmental compartments



SDS Number: 400001021215

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:
1.3	07.03.2022	400001021215

Date of last issue: 26.10.2020 Date of first issue: 06.12.2017

Print Date 17.06.2022

1,4-bis(2,3 epoxypropoxy)butane: Distribution among : Koc: 12.59 Method: OECD Test Guideline 121 environmental compartments 12.5 Results of PBT and vPvB assessment Product: Assessment This substance/mixture contains no components considered 2 to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. 12.6 Endocrine disrupting properties Product: The substance/mixture does not contain components Assessment 1 considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. 12.7 Other adverse effects Product: Additional ecological An environmental hazard cannot be excluded in the event of : information unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods	
Product :	Dispose of contents and container in accordance with all local, regional, national and international regulations. Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging :	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 3082
RID	:	UN 3082
IMDG	:	UN 3082





According	Y DATA SHEET to REACH Regulation (EC) N s SI 2019/758	lo 19	907/2006, as amended	by UK REACH	HUNTSMAN		
ARALI	ARALDITE® RAPID RESIN						
Version 1.3	Revision Date: 07.03.2022		OS Number: 0001021215	Date of last issu Date of first issu			
					Print Date 17.06.2022		
ΙΑΤΑ		:	UN 3082				
	roper shipping name	-					
ADR		:	ENVIRONMENTA N.O.S. (BISPHENOL A E		US SUBSTANCE, LIQUID,		
RID		:		ALLY HAZARDO	US SUBSTANCE, LIQUID,		
IMDG)	:	ENVIRONMENTA N.O.S. (BISPHENOL A E		US SUBSTANCE, LIQUID,		
ΙΑΤΑ		:	Environmentally h (BISPHENOL A E		ance, liquid, n.o.s.		
14.3 Trans	sport hazard class(es)						
ADR		:	9				
RID		:	9				
IMDO	;	:	9				
ΙΑΤΑ		:	9				
14.4 Pack	ing group						
Class Haza Label	ing group ification Code rd Identification Number s el restriction code		III M6 90 9 (-)				
RID Packi Class	ing group ification Code rd Identification Number	: : :	III M6 90 9				
Label	ing group	:	III 9 F-A, S-F				
Packi aircra Packi	ing instruction (LQ)	:	964 Y964 III Miscellaneous				
IATA Packi (pass Packi	(Passenger) ing instruction enger aircraft) ing instruction (LQ) ing group	:	964 Y964 III Miscellaneous				

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:
1.3	07.03.2022	400001021215

Date of last issue: 26.10.2020 Date of first issue: 06.12.2017

Print Date 17.06.2022

14.5 Environmental hazards

ADR Environmentally hazardous	:	yes
RID Environmentally hazardous	:	yes
IMDG Marine pollutant	:	yes
IATA (Passenger) Environmentally hazardous	:	yes
IATA (Cargo)		

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 **ENVIRONMENTAL** HAZARDS

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:			
DSL	: All components of this product are on the Canadian DSL		
	On the inventory, or in compliance with the inventory		
AIIC	: On the inventory, or in compliance with the inventory		
NZIoC	: On the inventory, or in compliance with the inventory		



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version 1.3	Revision Date: 07.03.2022	SDS Number: 400001021215	Date of last issue: 26.10.2020 Date of first issue: 06.12.2017
			Print Date 17.06.2022
ENCS		: On the inventory,	or in compliance with the inventory
KECI		: On the inventory,	or in compliance with the inventory
PICCS	3	: On the inventory,	or in compliance with the inventory
IECSC	2	: On the inventory,	or in compliance with the inventory
TCSI		: On the inventory,	or in compliance with the inventory
TSCA		: All substances lis	sted as active on the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302 H312 H315 H317 H318 H319 H332 H411 H412	 Harmful if swallowed. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. 			
Full text of other abbreviations				
Acute Tox.	: Acute toxicity			
Aquatic Chronic	: Long-term (chronic) aquatic hazard			
Eye Dam.	: Serious eye damage			
Eye Irrit.	: Eye irritation			
Skin Irrit.	: Skin irritation			
Skin Sens.	: Skin sensitisation			
Further information				

Classification of the mixture:



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ARALDITE® RAPID RESIN

Version 1.3	Revision Date: 07.03.2022	SDS Number: 400001021215	Date of last issue: 26.10.2020 Date of first issue: 06.12.2017
			Print Date 17.06.2022
Skin li	rrit. 2	H315	Calculation method
Eye Ir	rit. 2	H319	Based on product data or assessment
Skin S	Sens. 1	H317	Calculation method
Aquat	ic Chronic 2	H411	Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

